# DART SERVICE INSTRUCTION

TO AMEND INSTALLATION INSTRUCTIONS IIN-D130-701 REV. F AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D130-701 REV. 5 OR LATER APPROVED REVISION

REF. TCCA STC: SH94-14 REF. FAA STC: SR00213NY REF. EASA STC: 10016996 REF. ANAC STC: 2007S03-03

#### 1.0 PURPOSE

The purpose of this Dart Service Instruction (DSI) is to provide instructions to install the improved design D5359-041 Strut Assembly on the D130-701-043 Basket Installation at CHG 009 or later and the D130-701-041 Basket Installation at CHG 006 or later.

The improved D5359-041 Strut Assembly fits both LH and RH installations. Therefore, the D5359-042 Strut Assembly has been eliminated from the D130-701-043 kits at CHG 009 and later and the D130-701-041 kits at CHG 006 and later.

#### 2.0 INSTALLATION

- 1. Refer to IIN-D130-701 Rev F Figure 9 and replace with Figure 1 of this DSI.
- 2. Refer to IIN-D130-701 Rev F and replace sections 3.2.15 & 3.2.16 as follows:
  - 3.2.15 Locate the D5359-041 strut assembly as shown in Figure 9.
  - 3.2.16 Adjust the clevises at both ends of the strut to the appropriate length and angle to ensure that the MS17984-CXXX quick release pins can be engaged as shown in Figure 9 and install the MS17984-CXXX quick release pins. It is acceptable to flip orientation of the MS17984-CXXX Quick release pins to facilitate installation of the D5359-041 strut assembly.
  - 3.2.17 Torque the quantity (2) NAS509-6C jam nut per Table 1 (of IIN-D130-701). Check the witness holes on the strut to ensure that the threads on the clevises extend past the witness holes.
  - 3.2.18 Secure the NAS509-6C jam nuts to the AN3CH11A or AN3CH12A bolts using lock wire per AC43.13 or MS33540.
- Continue with remainder of installation starting at section 3.2.17 of IIN-D130-701 Rev F.

### 3.0 MAINTENANCE

- 1. Refer to ICA-D130-701 Rev 5 Figure 25-6 and add Figure 1 of this DSI as Figure 25-6C.
- 2. With reference to sections 25.2.5 and 25.6.4 of ICA-D130-701 Rev 5, install D5359-041 strut assemby on both LH and RH baskets for D130-701-041 at CHG 006 and subsequent and D130-701-043 at CHG 009 and subsequent
- 3. Maintain the improved D5359-041strut assembly per ICA-D130-701 Rev 5.

APPROVED


CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-0-01

APPROVED

BY:
D. SHEPHERD (DE # 02)

DATE:
CERT. NO.:
SH94-14
ISSUE NO.:
7

Α	NEW IS	SUE	AJS	16.12.22	
REV.		DESCRIPTION BY			DATE
DESIGN		AJS	DART AEROSPACE LTD		ľD
DRAWN	1	NO	HAWKESBURY, ONTARIO, CANADA		)A
CHECKED		AJS	DSI 9769		REV. A
MFG. APPR.		N/A			SHEET 1 OF 3
APPROVED		WM J	TITLE		SCALE
DE APPR.		D\$	STRUT INSTALLATIO	N	NTS
DATE 16.12.22			COPYRIGHT © 2016 BY DART AEROSPACE LTD.  THIS DOCUMENT IS PRIVATE AND COMFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS  NOT TO BE USED FOR ANY PURPOSE OR COPED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT  WRITTEN PERMISSION FROM DART AEROSPACE LTD.		



## **4.0 WEIGHT AND BALANCE**

There is a negligible weight and balance change associated with this modification.

## **5.0 PARTS LIST**

Update the Parts List in IIN-D130-701 Rev F and ICA-D130-701 Rev 5 as follows for D130-701-043 at CHG 009 or later and D130-701-041 at CHG 006 or later.

	Description	Part Number		QTY -041
	HELI-UTILITY-BASKET	D130-701-041		X
	HELI-UTILITY-BASKET	D130-701-043	X	
	STRUT ASSEMBLY	D5359-041	1	1
——————————————————————————————————————	STRUT ASSEMBLY	D5359-042	1	•
DELETI	BUSHING	D5367-1	1	

CANADA
DEPARTMENT OF TRANSPORT
AIRCRAFT CERTIFICATION
BRANCH
DAO # 01-O-01

BY:

D. SHEPHERD (DE # 02)

DATE: CERT. NO.: ISSUE NO.: 16.12.22 SH94-14 7

	DESIGN	AJS	DART AEROSPACE LTD		
PROVED	DRAWN	NO	HAWKESBURY, ONTARIO, CANADA		
	CHECKED	AJS	DRAWING NO.	REV. A	
	MFG. APPR.	N/A	DSI 9769	SHEET 3 OF 3	
	APPROVED	WM "	TITLE	SCALE	
	DE APPR.	DS	STRUT INSTALLATION	NTS	
ΔP	DATE 16.1	2 22	COPYRIGHT © 2016 BY DART AEROSPACE LTD.  THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS		